











Display

Toughened Glass




5.0 inch, Large and Easy-to-View LCD





Improved business operation by large display suitable for legible application





Toughness

Drop specifications

Drop 1.5m



Environmental specifications

IP65





Operating temperature specifications

-20°C to +50°C









Camera





Imager





Readable 1D and 2D codes covered with vinyl





Readable hard-to-read 1D and 2D codes

High Speed scanning C-MOS imager with laser aimer



Fading





Scratched

Soiling

Improved operation by C-MOS imager with the latest module and decoder

Battery (5800mAh)







- 1) Made in Japan battery cells
- 2) Slim design
- 3) One of the largest battery on the market
- 4) Longer operation time



RADIO










W-WAN

- LTE
- HSPA (HSUPA/ HSDPA)
- UMTS
- EGPRS (EDGE)
- GPRS
- GSM (E-GSM-900/ DCS-1800)



RADIO





W-LAN







Standards	Rate of transmission	Frequency	
IEEE802.11a	54Mbps	5GHz	
IEEE802.11b	11Mbps	2.4GHz	
IEEE802.11g	54Mbps	2.4GHz	
IEEE802.11n	72Mbps	2.4GHz 5GHz	



Bluetooth

Ver.4.1+EDR/LE:

- EDR (enhanced data rate)
- High speed
- Low energy
- Supports a lot of Bluetooth Profiles

Features

RFID/NFC reader/writer 13.56Mhz

ISO14443 Type A

ISO14443 Type B

ISO15693

Felica

1 SAM slot for data de- and encryption of NFC- and RFID tags

Log-in security by ID card



Security control with RFID tags



RADIO







Interfaces

USB Connection to PC

via 16pins I/O connector or via single slot communication cradle



microSD

Compatible with SDHC

SIM card

SIM compliant with ISO7816 (W-WAN model)

SAM slot

SAM slot for the NFC module


Measurements



Android 6.0.1



One of the first devices with Android 6.0.1 in the industrial area



Development Environment



Android Studio https://developer.android.com/studio/index.html

API Level	Android Version		Casio	Competitors	
23	6.0 / 6.0.1	Marshmallow	IT-G400 ←	Zebra Honeywell	TC 51 / 56 Dolphin CT50 / 75e
21/22	5.0/5.1	Lollypop		Pidion M3 Mobile	EF 500R / 400 SM10 LTE
19	4.4	KitKat		Zebra Pidion	TC75 BM 180 / BP 30
16/17/18	4.1/4.2/4.3	Jelly Bean		Zebra M3 Mobile	MC40 SM10
15	4.0	Ice Cream Sandwich	V-T500	Honeywell	70e

For IT-G400

Device Control Libraries will be provided from Casio (Imager, Hard Keys, etc.)

Specification



Item Specification

OS Android 6.0.1
CPU Oualcomm 1.:

Qualcomm 1.2 GHz Quad core

2GB 16GB

F-ROM 16GE LCD 5.0 in

RAM

Camera

Scanner Touch panel

W-LAN

GPS

NFC W-WAN

USB

Weight

Bluetooth

Earphone/MIC Jack

Extension memory

Main battery

Dimension

Encryption

Bundled items

5.0 inch transmissive color TFT diplay (720x1,280dots)

Rear 8M pixels / Front 2M pixels

C-MOS imager

Capacitive touch panel W-LAN(801.11a/b/g/n)

Ver. 4.1 + EDR/LE

GPS (depends on model)

ISO14443 Type-A/Type-B, Felica, ISO15693

LTE/WCDMA/GSM (depends on model)

3.5mm

USB 2.0 High-speed

microSD slot x1

Lithium-Ion battery (5,800mAh)

approx. 325g

approx. 82mm x 158mm x 24mm

Lithium-Ion battery, Wrist Strap, Stylus pen, AC adapter, Screen

protect sheet

1 SAM slot





Retail

Inventory

Indoor

Manufacturing

Industry

Health Care













POD

Transport

Ticketing

SFA

FFA

Parking Enforcement

Outdoor



Usable Google apps with Google Mobile Service



Available to use the commercial apps and various Google apps.

- Google Map
- G-Mail
- Google Drive
- Hangout
- Chrome
- Google Play



European Support Team based in Germany



Short Response Times



Exclusive Knowledge Base



75 Years of Experience



Requirements for industrial Handheld Terminals

IT-G400

Drop durability

Integrated C-MOS imager

Minimum 3 years of product supply period

Spare parts availability: 5 years after product discontinuation


Large battery

Long operating time





European and Local Support available





System Configuration



IT-G400-xxL : Battery, battery cover, screen protect sheet, stylus pen, wrist strap, and AC adapter



Model List

Model	Specification	
IT-G400-C21L	W-LAN, battery	
IT-G400-WC21L	W-WAN, battery	



IT-G400

Options



USB cradle + battery charger: HA-R60IO



4-slot cradle-type charger: HA-R38CHG



4-slot battery charger: HA-R34CHG



Cable between Serial (IT-G400) and USB: HA-R81USBC



Power supply: AD-S10050B

Bundled Set

IT-G400-xxL: Battery, battery cover, screen protect sheet, stylus pen, wrist strap, and AC adapter



Model List

Model Specification

IT-G400-C21L W-LAN, battery

IT-G400-WC21L W-WAN, battery

System Configuration



IT-G400-xxL : Battery, battery cover, screen protect sheet, stylus pen, wrist strap, and AC adapter



Model List

Model	Specification	
IT-G400-C21L	W-LAN, battery	
IT-G400-WC21L	W-WAN, battery	



IT-G400

Options



USB cradle + battery charger: HA-R60IO



4-slot cradle-type charger: HA-R38CHG



4-slot battery charger: HA-R34CHG



Cable between Serial (IT-G400) and USB: HA-R81USBC



Power supply: AD-S10050B

Accessories

Model	Description
HA-R21LBAT HA-R60IO HA-R38CHG HA-R34CHG	Battery pack (5800mAH) USB cradle + battery charger (with AC adapter, USB cable) 4-slot cradle-type charger (with AC adapter) 4-slot battery charger (with AC adapter)
HA-R81USBC HA-R95PS10	Cable between Serial (IT-G400) and USB Screen protect sheet (10 sheets)
AD-S10050B	5V AC adapter for IT-G400 (with AC plug EU/US/UK)



